

www.bitunamel.de



BITUNAMEL
FELDMANN

MULTICAT
NOORCAT



BITUNAMEL FELDMANN

TECHNICAL SPECIFICATION

Build:	2010	
Classification:	BV Hull-Mach / Tug Unrestricted navigation / AUT-UMS	
GRT:	107	
Dimensions:	LoA: 24,00 m Breadth: 9,00 m Draft: 3,30 m min / 2,50 m	1,6 tons @ 12,50 m moonpool 1000 mm x 700 mm free working deck, wood covered, 10 tons/m
Propulsion:	2 x Caterpillar 3412D TTA/B, 1.696 bhp @ 1.800 rpm 2 x Reintjes WAF 464 2 x Ice strengthened FPP in nozzles	Transfer pumps: Fuel supply 50 cbm / hr @ 4,8 bar Fresh water supply 50 cbm / hr @ 4,8 bar
Auxiliary:	Caterpillar C-09, with 162 KW hydraulic power pack Caterpillar C-04.4T 2 x 63,8 kVA, 400 V	Bridge & Communication: According GMDSS "A1"+"A2" 2 VHF, 1MF Inmarsat-C Navtex Radar (ATA, ARPA) GPS AIS Autopilot Echosounder Magnet compass Satellite compass Chart plotter 2 Searchlights GSM and Sat phone
Speed:	10 kn	
Bollard pull:	24 to cert., max 26 to	
Deck equipment:	double drum AH towing winch, 600 m / 30 mm, 300 m / 32 mm 30 tons @ 6 m/min., 6 tons @ 24 m/min towing hook tugger winch 8 tons @ 4,5 m/min bow and stern roller 25 tons each front deck crane HEILA HLRM 140-4S 8,1 tons @ 14,10 m Aft deck crane HEILA 25-4S	Accommodation: 3 x single cabins 1 x double cabin option for one 20' living container (DNV-GL class approved)

BITUNAMEL FELDMANN GMBH

Adress: Zur Teerhofinsel 2, 23554 Lübeck
Phone: +49 (0)451 289950

Fax: +49 (0)451 283721
E-Mail: info@bitunamel.de
Web: http://www.bitunamel.de